

Envirolite Paint Disposal System

WARNING: THIS MACHINE IS STRICTLY FOR WATERBASED PRODUCTS ONLY!

BASIC WASHING PROCEDURE

- 1) Place plug into the machine's basin.
- 2) Wash brushes, rollers etc with water in the basin.
- 3) Wash and rinse out basin to ensure it stays clean and unclogged.

MAIN SYSTEM CLEANSE

Once the tank has reached the max level, which is just below the inlet from the top basin, the following cleansing procedure is to be taken:

- 1) Add two litres of **Floc 1** into the main tank, and stir vigorously for five minutes with a plunger.
- 2) After mixture has been thoroughly stirred, add one litre of **Floc 2** and stir again for a further three minutes.
- 3) The material is then to be left at least overnight, or for 24 hours to allow optimum result.
- 4) Open tap, which is located on the water filter, and allow water to run into the sewer.
- 5) The sludge which is left over, after all the water has drained, is to be pumped into the filter bag/s.
- 6) Once all sludge has been pumped and the tank is completely empty, the filter bags are to be emptied into the empty buckets provided.
- 7) A Fill One representative will remove buckets from site.

PLEASE NOTE: This machine is not to be used as a refuse bin for food waste or any other waste material as this will result in machine clogging and costly damage.